

## PRODUCT UPDATE

### LIGHT TRAILER BEARING KITS



**WARRANTY:**  
24 Months / 40,000kms

The BW range of trailer bearing kits is developed to suit all types of towing applications, including boat and jet ski trailers which are often exposed to salt water. Trailer bearings are essential as they allow the wheels to rotate freely with minimal friction and support the weight of the trailer.

The BW trailer bearing kits are sourced from top-tier manufacturers to ensure safety and reliability. The kits are available in a range of bearing types and oil seals to suit road, off-road and marine use.

#### PRODUCT FEATURES

1. Extensive range of bearing kits to suit all common trailer applications including marine.
2. Kits come complete with inner and outer bearing, oil seal and split pin.
3. Premium quality bearings from top-tier manufacturers.
4. Available in standard and marine type oil seals.

#### TECH TIPS

#### IDENTIFYING THE BEARINGS ON YOUR TRAILER HUB

Your trailer hub has two tapered roller bearings, an inner bearing, and an outer bearing. And each bearing has a cup that fits inside the hub and a cone that slides over the axle.

Always replace the bearings as a set with the cup and cone together. They can be identified by the part number stamped on the cup and cone (see below images). The part number on the cone and the last two digits on the cup, make up the full part number of the bearing (i.e., LM67048/10).

You can also measure the bearings to find the correct type for your trailer. Listed below are the common trailer bearing combinations.



TYPE	INNER BEARING NO.	INNER BEARING ID X OD X WIDTH (mm)	OUTER BEARING NO.	OUTER BEARING ID X OD X WIDTH (mm)
LM (HOLDEN)	LM67048/10	31.750 x 59.131 x 15.875	LM11949/10	19.050 x 45.237 x 15.494
SLIMLINE (FORD)	L68149/10	34.989 x 59.131 x 15.875	LM12749/10	21.986 x 45.237 x 15.494
COMPOSITE	LM67048/10	31.750 x 59.131 x 15.875	LM12749/10	21.986 x 45.237 x 15.494
PARALLEL	L68149/10	34.989 x 59.131 x 15.875	L68149/10	34.989 x 59.131 x 15.875
STANDARD 2T	25580/20	44.450 x 82.931 x 23.813	LM67048/10	31.750 x 59.131 x 15.875
STANDARD 3T	30210	50.000 x 90.000 x 21.750	LM29749/10	38.100 x 65.088 x 18.034
DEXTER 1.8T / D35 USA	L68149/11	34.989 x 59.974 x 15.875	L44649/10	26.988 x 50.292 x 14.224
DEXTER D44 USA	L68149/11	34.989 x 59.974 x 15.875	LM67048/10	31.750 X 59.131 X 15.875
DEXTER 2T / D60 USA	25580/20	44.450 x 82.931 x 23.813	15123/245	31.750 X 61.999 X 18.161
DEXTER HUB 8-91A USA	L44643/10	25.400 x 50.292 x 14.224	L44643/10	25.400 x 50.292 x 14.224
DEXTER USA	L44649/10	26.988 x 50.292 x 14.224	L44649/10	26.988 x 50.292 x 14.224
AL-KO 1.5T	LM29749/10	38.100 x 65.088 x 18.034	LM67048/10	31.750 x 59.131 x 15.875
AL-KO 2T	30210	50.000 x 90.000 x 21.750	15123/245	31.750 x 61.999 x 18.161
AL-KO 3T	30210	50.000 x 90.000 x 21.750	LM29749/10	38.100 x 65.088 x 18.034